



Revolabs HD Venue

Rack-Mounted Dual Channel Microphone System

THE PERFECT RACK-MOUNTED SOLUTION FOR VOICE APPLICATIONS

The Venue™ Dual Channel, rack-mounted wireless microphone system is the perfect audio solution for video conferencing or voice reinforcement applications. Its rack-mounted design allows you to integrate the Venue easily into video conferencing products, or audio equipment.

The Venue Dual Channel wireless system consists of a rack-mountable base station, and an HD wireless microphone charger base, available in single and dual channel models.

The Venue supports up to two HD audio wireless microphones. With frequency groups, the Venue allows for installation of two Venue systems with a maximum of four microphones in the same area.

As with the other HD systems, the Venue system provides bi-directional audio, which allows audio to be sent back to the microphone so that users can listen using a headset.

The Venue Dual Channel takes advantage of the same technology available for boardrooms and large conference rooms in the Executive HD products. Utilizing Revolabs "Designed For Speech" technology, the Venue provides wideband frequency to improve the intelligibility and presence of speech, allowing the system to

pick up the entire human voice spectrum. This technology consists of proprietary audio processing algorithms resulting in accurate reproduction of human speech. The Venue wireless microphone system is managed through a series of dip switches allowing users to control the different audio options. The switches also enable selection of the level of the outputs, line level, or microphone level. In the Dual Channel system users can select whether the microphone channels are mixed in the base unit to provide a mixed output, or whether the two channels are handled independent of each other, providing two separate outputs and inputs for the two channels. All Revolabs HD wireless microphones include RF Armor™ technology, which enables the microphone to operate cleanly even when in direct contact with other wireless electronic devices known to cause unwanted audio interference, such as GSM mobile phones, smart phones, etc. Fail-safe security is integrated with all Revolabs wireless microphones because they use 128-bit encryption to prevent anyone from listening in on conversations. Additional settings let users control the transmission power mode used by the receiver, providing a higher density of HD systems in a given area where a lot of systems are required. The adjustable power reduces interferences between the systems.

The Venue can be mixed and matched with a

variety of HD wireless microphones. Offered separately, the microphones are sleek in design and come in several styles: wearable, tabletop directional, tabletop omni-directional, XLR Adapter for handheld microphones, and adapters for Countryman™ microphones. Revolabs microphones and adapters are very easy-to-use. Just remove the microphone from the charger base, un-mute and talk.

Additional benefits include a rechargeable battery providing up to eight hours of talk time on a full charge, and only taking approximately two hours to fully charge a battery. Best of all, the system is wireless. Enterprise users can move about their conference room and still be heard!

BENEFITS

Superior Audio Quality

Wideband frequency response provides high definition audio delivering spoken word clarity

Wireless Freedom

Lets users sit anywhere within a conference room or walk around freely

Support for Multiple Microphones

Wearable, tabletop boundary and handheld as well as Countryman Adapter for earset microphone

No More Cell Phone Buzz

RF Armor technology lets microphones operate even when in direct contact with other wireless electronic devices

Secure

128-bit encryption prevents unwanted users from listening in



AUDIO	Channels	2 channels per system
	Radio Frequency	North and South America: 1920 to 1930 MHz Africa, Asia, Australia and Europe: 1880 to 1900 MHz (DECT EU) Mainland China: 1900 to 1920 MHz Japan: 1893.5 to 1906.1 MHz
	Range	300 feet (90 meters) approx. (no obstruction) Out-of-range alarm
	Bandwidth	50-14,000 Hz
BASE STATION	Power	5V DC, 1A locking power connector 100-240V, 50-60 Hz; Power Supply included
	Connectors/Interfaces	Channel LED indicators Pairing Push Buttons USB port for firmware update only Configuration DIP Switches (8) Channel 1 Analog Output 1/4 inch or male XLR jacks Channel 2 Analog Output 1/4 inch or male XLR jacks Channel 1 Analog Input 1/4 inch/XLR combo jacks Channel 2 Analog Input 1/4 inch/XLR combo jacks
CHARGER BASE	Power	5V DC, 1A 100-240V, 50-60 Hz; Power Supply included
	Connectors	2 proprietary 4 pin microphone charge jacks



SHARING PASSION & PERFORMANCE

Yamaha Unified Communications, Inc.

144 North Road #3250
Sudbury, MA 01776 USA
+1 800-326-1088
uc-sales@music.yamaha.com

Yamaha UC EMEA

190 High Street Tonbridge, Kent
TN9 1BE, UK
+44 (0)1732 366535
uc-salesemea@music.yamaha.com

Yamaha UC APAC

+852.8108.8820
uc-salesapac@music.yamaha.com