Certificate of Constancy of Performance

0359-CPR-00406



In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation), this certificate applies to the construction product(s).

Product(s):	VXS Range of Wall Mounted Loudspeakers (refer to attached appendix for details and conditions)
Produced by or for:	Yamaha Corporation 10-1, Nakazawa-cho, Naka-ku, Hamamatsu-shi, Shizuoka 430-8650, Japan
Produced in the manufacturing plant(s):	P.T. Yamaha Electronics Manufacturing Indonesia (YAMAHAID.01) Kawasan Industri PIER (Kawasan Berikat Nusantara), Jalan Rembang Industri II/9-11, Mojoparon-Rembang, Pasuruan 67152, Indonesia
Intended use:	Fire Safety

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s):

EN54-24:2008

Fire detection and fire alarm systems. Components of Voice Alarm Systems - Loudspeakers

Under system 1 are applied and that the product(s) fulfils all the prescribed requirements set out above.

This certificate was first issued on 7th **November 2014** and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly, unless suspended or withdrawn by the product certification body. A review of the product(s) and compliant standard(s) will be carried out after 5 years to ensure continued compliance.

Notified Body 0359

Intertek Testing & Certification Limited Cleeve Road, Leatherhead Surrey, KT22 7SB Tel: + 44 (0)1372 370900 Fax: +44 (0)1372 370977 E-mail: cpd.uk@intertek.com

www.intertek.com

Daniel Griffin Certification Manager

D-8

Date 19/12/2014 Issue 2

Re-Issue 07/11/2019

Registered No 3272281 Academy Place, 1-9 Brook Street, Brentwood, Essex, CM14 5NQ, United Kingdom

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Certificate of Constancy of Performance 0359-CPR-00406



Appendix to Certificate of Constancy of Performance 0359-CPR-00406

The details and condition of use for the VXS Range of Wall Mounted Loudspeakers, placed on the market by:

Yamaha Corporation

10-1, Nakazawa-cho, Naka-ku, Hamamatsu-shi, Shizuoka 430-8650, Japan

To be used in accordance with the supplier's installation instructions and in conjunction with the following bases, ancillaries, sounder tones and sensitivity settings (*where applicable*):

Products compliant with EN54-24:2008

Variant	Manufacturing Location	Description
VXS5-VA	YAMAHAID.01	30 W, black, plastic moulded, wall mounted loudspeaker with a 4.7uF capacitor
VXS5-VAW	YAMAHAID.01	30 W, white, plastic moulded, wall mounted loudspeaker with a 4.7uF capacitor
VXS8-VA	YAMAHAID.01	60 W, black, plastic moulded, wall mounted loudspeaker with a 3.3uF capacitor
VXS8-VAW	YAMAHAID.01	60 W, white, plastic moulded, wall mounted loudspeaker with a 3.3uF capacitor

Approved settings:

The following line voltage and power tap settings have been approved:-

	Model VXS5-VA and Model VXS5-VAW	Model VXS8-VA and Model VXS8-VAW	
Line Voltage	Power Tap	Power Tap	
70V	30W, 15W, 7.5W, 3.8W	60W, 30W, 15W, 7.5W	
100V	30W, 15W, 7.5W	60W, 30W, 15W	

The following impedance (transformer bypass) setting has been approved:-

	Model VXS5-VA, Model VXS5-VAW, Model VXS8-VA and Model VXS8-VAW		
Impedance	8Ω		

Conditions of use:

Suitable for outdoor (Type B) applications

General notes:

- 1. Evaluated under Intertek project number 101440203.
- 2. <u>No CE or other type approval is made or inferred outside of the attestation of conformity and the product</u> performance as stipulated on this certificate.

Intertek Testing & Certification Limited, Cleeve Road, Leatherhead, Surrey, KT22 7SB Tel: + 44 (0)1372 370900, Fax: +44 (0)1372 370977, E-mail: <u>cpd.uk@intertek.com</u>

0359-CPR-00406 Issue 2

www.intertek.com

Registered No 3272281 Academy Place, 1-9 Brook Street, Brentwood, Essex, CM14 5NQ, United Kingdom

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Certificate of Constancy of Performance 0359-CPR-00406



Appendix to Certificate of Constancy of Performance 0359-CPR-00406 (continued)

Table of performance for EN54-24:2008						
Harmonised technical specification						
Essential characteristics	Performance	Clauses	Notes			
Performance under fire condition.	Pass	4.2, 5.2, 5.3, 5.4, 5.5	а			
Operational reliability	Pass	4.3, 4.4, 4.5, 5.6, 5.18	b			
Durability of operational reliability: temperature resistance	Pass	5.7, 5.8, 5.9	b			
Durability of operational reliability: humidity resistance	Pass	5.10, 5.11, 5.12	b			
Durability of operational reliability: corrosion resistance	Pass	5.13				
Durability of operational reliability: impact and vibration resistance	Pass	5.14, 5.15, 5.16, 5.17	с			
Notes:						

- - - -

a. The products covered by this standard are assumed to enter the alarm condition, in an event of fire, before the fire becomes so large as to affect their functioning. There is therefore no requirement to function when exposed to direct attack from fire.

- b. For Clauses 5.7, 5.9, 5.10 and 5.18, Type B conditioning was applied.
- c. Model VXS8-VA and Model VXS8-VAW exceed 4.75kg in weight; an assessment to Clause 5.14 was therefore not performed on these models.

Intertek Testing & Certification Limited, Cleeve Road, Leatherhead, Surrey, KT22 7SB Tel: + 44 (0)1372 370900, Fax: +44 (0)1372 370977, E-mail: <u>cpd.uk@intertek.com</u>

0359-CPR-00406 Issue 2

www.intertek.com

Registered No 3272281 Academy Place, 1-9 Brook Street, Brentwood, Essex, CM14 5NQ, United Kingdom

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.